

KSV 45/2 W

Wet & Dry and Swarf Vacuum Cleaners

The KSV 45/2 W is a portable industrial unit designed to pick up engineering coolant (suds) and metal chippings (excluding spirals).

The motor unit is protected by a ball float system to cut off the suction - preventing over filling of the canister with liquid. The float cage is surrounded with a perforated steel filter to prevent swarf being sucked into the vacuum motors.

A perforated steel basket that holds the metal chippings/swarf sits inside the canister. A lifting handle makes it easy to remove for emptying, whilst a drain hose and stopper enable all liquid to easily be drained from the canister.

FEATURES

Supplied with either a 38mm or 51mm hose and tool kit comprising of:

- 38mm x 3m heavy duty polyurethane hose
- 38 x 540mm stainless steel crevice tool
- 38 x 305mm stainless steel gulper/scrapper tool
- 51mm x 3m heavy duty polyurethane hose
- 51 x 600mm stainless steel crevice tool
- 51 x 300mm stainless steel gulper/scrapper tool.

Kerstar swarf vac - **KSV**

Capacity of can/basket in litres - **40**

No. of motors in motor head - **2**

Fitted with wet cut off device & swarf filter - **W**

Supply voltage - **230V**

(Also available in 110V).



KSV 45/2 W

TECHNICAL SPECIFICATION

MOTOR

2 x 1,000W bypass cooling (2,000W Max - 1,600W Mean)

POWER

230V 50Hz / 110V 50/60Hz

PERFORMANCE (230V & 110V)

Max. Vacuum - 2,200mm

Max. Airflow - 295 m³/Hr

CAPACITY

Max. Solids only capacity - 32L

Max. Liquids only capacity - 40L

DIMENSIONS (H X W X D)

1120x460x520mm

WEIGHT

Machine only (no hose or tools) - 30KG



KSV 45/2 W



www.kerstar.co.uk

sales@filtermist.com +44 (0) 1952 290500

Kerstar products are manufactured by Filtermist International Limited.

 **FILTERMIST**