

TECHNICAL DATA











INFO@COYNCO.COM

- 2-3 By-pass motors or three-phase turbine for maximum versatility in electrical power supply.
 Industrial vacuum cleaner for the suction of oils and chips in the mechanical industry.
- Automatic shutdown with electric float at maximum filling level.

ТҮРЕ	OIL
PRODUCT	OIL 140 3M P
VACUUMED MATERIAL	Oil and metal shavings
MOTORIZATION	Nr 3 By-pass
POWER	3300 W
VOLTAGE	230 V
FREQUENCY	50 / 60 Hz
AMPS	14,4 A
AIR FLOW	510 m3/h
DEPRESSION	230 mBar
VALVE DEPRESSION	-
SUCTION INLET	Type B - 60 mm
DIMENSIONS	68 x 80 h152 cm
WEIGHT	80 Kg
FILTER CHAMBER DIAMETER	Ø 460 mm
FILTER TYPE	Cartridge M Class Hydro-Oleophobe
FILTERING SURFACE	-
FILTER CLEANING	-
FIRST FILTRATION STAGE	Oleophobic Sponge
LIQUIDS CAPACITY	140 Liters
SOLIDS CAPACITY	35 Liters
OIL FILTRATION GRADE	Nylon 300 µ
ELECTRIC FLOATER	YES Automatic shut OFF
DISCHARGE SYSTEM	Electric PUMP 220 Lt/min (550W - 230V)





TYPE NO. BOX PALLET

NO. MACHINES

DIMENSIONS PACKAGE 90x70 h190 cm

WEIGHT

90/110

) cm

90x70 h200 cm

All information in this document is subject to change without notice.