







INFO@COYNCO.COM

- 5.5 kW two-stage turbine with thermal protection for powerful suction capacity.
- Suitable for continuous 24/7 operation without maintenance, for long operational life
- Industrial vacuum cleaner with cartridge filtering system more suitable for dust suction than conventional polyester star filters

TYPE	PRO
PRODUCT	HDC 155 P PRO
VACUUMED MATERIAL	Dust
MOTORIZATION	Turbine
POWER	5,5 kW
VOLTAGE	400 V
FREQUENCY	50 Hz
AMPS	10,4 A
AIR FLOW	560 m3/h
DEPRESSION	320 mBar
VALVE DEPRESSION	250 mBar
SUCTION INLET	Type B Tangential - 60 mm
DIMENSIONS	120X60 h135 cm
WEIGHT	151 Kg
FILTER CHAMBER DIAMETER	Ø 460mm
TANK AND LONGOPACK INTERCHANGEABILITY	Yes
DISCHARGE SYSTEM	100 Liters / Longopac®
FILTER TYPE	Cartridge - M Class Conductive alluminized
FILTERING SURFACE	22.000 cm2
FILTER CLEANING	Semi-automatic Pneu-mechanical Shaker
HEPA ABSOLUTE FILTER	-

PACKAGING



TYPE	NO. MACHINES
вох	1
PALLET	1
PALLET	-

DIMENSIONS PACKAGE	WEIGHT
90X70 H190 CM	-
90X70 H200 CM	170 KG
-	-