



Part of Absolent  
Air Care Group

**Kerstar Dry Vacuum Cleaners Range Product Comparison Matrix**

| Vacuum Type | ATEX Zone | Model    | Power                          | Canister type                  | Single Motor / Performance   | Twin Motor / Performance                           | Triple Motor / Performance                       | Capacity (wet/dry) - Litres                          | Dimensions (H) x W x D mm      | Weight (kg) Single / Twin Motor | Weight (kg) Twin / Triple Motor | Cleaning range      |                       |
|-------------|-----------|----------|--------------------------------|--------------------------------|--|--|--|--|--------------------------------|---------------------------------|---------------------------------|---------------------|-----------------------|
| Dry         | N/A       | KV 5     | Electric - 230/110v or 50/60Hz | Steel/Powder coated            | 1000w Max / 800w Mean<br>Max Airflow - 43.5Ltr/Sec<br>Max Vacuum - 2,500mm | N/A  | N/A  | 8.5L   | (in carry case)<br>430x350x420 | 9                               | N/A                             | 27 Metres / 88 Feet |                       |
|             |           | KV 10    |                                | Steel/Powder coated            |  |  |  | 8.5L   | 425x380x380                    | 8.75                            |                                 |                     |                       |
|             |           | KV 15    |                                | Stainless steel                |  |  |  | 9L   | 470x375x375                    | 9                               |                                 |                     |                       |
|             |           | KV 18/1  |                                | Stainless steel                |  |  |  | 23L  | 895x410x420                    | 14.5                            |                                 |                     |                       |
|             |           | KV 20    | Stainless steel                | Electric - 230/110v or 50/60Hz | Plastic injection moulded  | 1000w Max / 800w Mean<br>Max Airflow - 43.5Ltr/Sec | 2000w Max, 1600w Mean<br>Max Airflow - 82Ltr/Sec | N/A  | 20L                            | 610x440x440                     | 12.5/15.5                       | N/A                 | 28.5 Metres / 94 Feet |
|             |           | KV 25    | 23L                            |                                |  |  |  |  | 610x440x440                    | 12.0/15.0                       |                                 |                     |                       |
|             |           | KV 30    | Stainless steel                |                                |  |  |  |  | 30L                            | 710x440x440                     | 13.0/16.0                       |                     |                       |
|             |           | KV 45    | Stainless steel                |                                |  |  |  |  | 40L                            | 865x450x460                     | 13.75/20                        |                     |                       |
|             |           | KV 50    | Plastic injection moulded      | Electric - 230/110v - 50Hz     | Steel  | N/A  | 2000w Max, 1600w Mean<br>Max Airflow - 82Ltr/Sec | 3x1000w Max / 2400w Mean<br>Max Airflow - 113Ltr/Sec | 40L                            | 920x520x560                     | 18.5/21.5                       | N/A                 | 29.5/32               |
|             |           | KV 65    | 88L                            |                                |  |  |  |  | 1060x540x610                   | 30/32.5                         |                                 |                     |                       |
|             |           | KV 110   | 86L                            |                                |  |  |  |  | 730x490x490                    | 21.6                            | N/A                             |                     |                       |
|             |           | KV 90    | Plastic Injection moulded      | Electric - 230/110v - 50Hz     | 1000w Max / 800w Mean<br>Max Airflow 43Ltr/Sec, Max Vacuum 2,500mm         | N/A  | N/A  | N/A  | 56L                            | 895x540x610                     | N/A                             | N/A                 | 27 Metres / 88 Feet   |
|             |           | Prima    |                                |                                |  |  |  |  | 8L                             | 425 x 355 x 375                 | 6.9                             |                     |                       |
|             |           | Prima CD |                                |                                |  |  |  |  | 490 x 355 x 375                | 7.7                             |                                 |                     |                       |
|             |           | Max      |                                |                                |  |  |  |  | 330x335x370                    | 6.7                             |                                 |                     |                       |
|             |           | Max CD   | 370x335x370                    | 7.4                            |  |  |  |  |                                |                                 |                                 |                     |                       |